



Test Report: LPF-25D-30

25W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|--------------------------|--|---|--|---------|
| 1 | RIPPLE & NOISE | V1 : 200 mVp-p (Max) | I/P : 230VAC O/P : FULL LOAD Ta : 25°C | V1 : 60 mVp-p (Max) | P |
| 2 | CONSTANT CURRENT REGION | V1= 15V-30V | I/P : 230VAC O/P : CV MODE Ta : 25°C | O/P= 15V : 0.847 A O/P= 29V : 0.849 A | P |
| 3 | OUTPUT VOLTAGE TOLERANCE | V1 : 4 %~ -4 % (Max) | I/P : 100 VAC / 305 VAC O/P : FULL/ MIN LOAD Ta : 25°C | V1 : 0.137 %~ -0.043 % | P |
| 4 | LINE REGULATION | V1 : 0.5 %~ -0.5 % (Max) | I/P : 100 VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C | V1 : 0.007 %~ -0.003 % | P |
| 5 | LOAD REGULATION | V1 : 0.5 %~ -0.5 % (Max) | I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C | V1 : 0.043 %~ -0.043 % | P |
| 6 | SET UP TIME | 230VAC : 500 ms (Max) 115VAC : 1500 ms(Max) | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 287.592 ms 115VAC/ 235.137 ms | P |
| 7 | RISE TIME | 230VAC : 80 ms (Max) 115VAC : 80 ms (Max) | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 13 ms 115VAC/ 14 ms | P |
| 8 | HOLD UP TIME | 230VAC : 16 ms (TYP) 115VAC : 16 ms (TYP) | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 76 ms 115VAC/ 77 ms | P |
| 9 | OVER/UNDERSHOOT TEST | < ±5% | I/P : 230 VAC O/P : FULL LOAD Ta : 25°C | TEST : <5 % | P |
| 10 | DYNAMIC LOAD | V1 : 3000 mVp-p | I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C | (1) 576 mVp-p (2) 720 mVp-p | P |

| | | | | | | | | | | | | |
|--|------------------|---|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| 11 | DIMMER TEST | SPEC: | | | | | | | | | | |
| | | *Output constant current level can be adjusted through output cable by 1 ~ 10Vdc, PWM signal or resistor between ADJ1(+) and ADJ2(-). | | | | | | | | | | |
| | | *Reference resistance value for output current adjustment (Typical) | | | | | | | | | | |
| | | Resistance value | 10K | 20K | 30K | 40K | 50K | 60K | 70K | 80K | 90K | 100K |
| | | Output current | 10% | 20% | 30% | 40% | 50% | 60% | 70% | 80% | 90% | 100% |
| | | *1 ~ 10V dimming function for output current adjustment (Typical) | | | | | | | | | | |
| | | Dimming value | 1V | 2V | 3V | 4V | 5V | 6V | 7V | 8V | 9V | 10V |
| | | Output current | 10% | 20% | 30% | 40% | 50% | 60% | 70% | 80% | 90% | 100% |
| | | *10V PWM signal for output current adjustment (Typical) | | | | | | | | | | |
| | | Duty value | 10% | 20% | 30% | 40% | 50% | 60% | 70% | 80% | 90% | 100% |
| | | Output current | 10% | 20% | 30% | 40% | 50% | 60% | 70% | 80% | 90% | 100% |
| TEST RESULT: I/P : 230 VAC ; Ta : 25°C | | | | | | | | | | | | |
| 1 | Resistance value | 10K | 20K | 30K | 40K | 50K | 60K | 70K | 80K | 90K | 100K | |
| | Output current | 0.070A | 0.157A | 0.244A | 0.324A | 0.408A | 0.501A | 0.585A | 0.672A | 0.757A | 0.839A | |
| | % | 8.33% | 18.69% | 29.05% | 38.57% | 48.57% | 59.64% | 69.64% | 80.00% | 90.12% | 99.88% | |
| 2 | Dimming value | 1V | 2V | 3V | 4V | 5V | 6V | 7V | 8V | 9V | 10V | |
| | Output current | 0.073A | 0.159A | 0.246A | 0.332A | 0.419A | 0.506A | 0.592A | 0.679A | 0.765A | 0.843A | |
| | % | 8.57% | 19.43% | 29.90% | 40.00% | 50.19% | 60.76% | 70.86% | 80.67% | 90.86% | 100.3% | |
| 3 | Duty value | 10% | 20% | 30% | 40% | 50% | 60% | 70% | 80% | 90% | 100% | |
| | Output current | 0.073A | 0.159A | 0.246A | 0.332A | 0.419A | 0.506A | 0.592A | 0.679A | 0.765A | 0.843A | |
| | % | 8.69% | 18.93% | 29.29% | 39.52% | 49.88% | 60.24% | 70.48% | 80.83% | 91.07% | 100.4% | |

P

INPUT FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|-----------------------|---|---|--|---------|
| 1 | INPUT VOLTAGE RANGE | 100VAC~305 VAC | I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V=97 V HIGH-LINE=305 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE) | 85 V~305V TEST : OK | P |
| 2 | INPUT FREQUENCY RANGE | 47HZ ~63 HZ NO DAMAGE OSC | I/P : 100 VAC ~ 305 VAC O/P : FULL-MIN LOAD Ta : 25°C | TEST : OK | P |
| 3 | POWER FACTOR | 0.95 / 230 VAC(TYP) 0.97 / 115 VAC(TYP) 0.92 / 277 VAC(TYP) | I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C | PF= 0.957 / 100% PF= 0.996 / 100% PF= 0.928 / 100% | P |
| 4 | EFFICIENCY | 85.5% (TYP) | I/P : 230 VAC O/P : FULL LOAD Ta : 25°C | 85.88 % | P |
| 5 | INPUT CURRENT | 230V/ 0.25 A (TYP) 115V/ 0.4 A (TYP) 277V/ 0.2 A (TYP) | I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C | I = 0.140 A/ 230 VAC I = 0.247 A/ 115 VAC I = 0.121 A/ 277 VAC | P |
| 6 | INRUSH CURRENT | 230V/ 50 A (TYP) COLD START | I/P : 230 VAC O/P : FULL LOAD Ta : 25°C | I = 36.6 A/ 230 VAC | P |
| 7 | LEAKAGE CURRENT | < 0.75 mA / 240 VAC | I/P : 240 VAC O/P : Min LOAD Ta : 25°C | L-CASE : 0.003 mA N-CASE : 0.003 mA | P |

PROTECTION FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|-----------------------------|--|---|---|---------|
| 1 | OVER LOAD PROTECTION | 95 % ~ 108 % | I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C | 101.26%/ 230 VAC 101.88%/ 115 VAC Constant Current Limiting ,recovers automatically after fault condition is removed. | P |
| 2 | OVER VOLTAGE PROTECTION | CH1 : 34 V ~ 40 V | I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C | 37.18 V/ 230 VAC 37.18 V/ 115 VAC Shut down and latch off o/p voltage, re-power on to recover | P |
| 3 | OVER TEMPERATURE PROTECTION | SPEC : TSW1 : 95± 5°C O.T.P. NO DAMAGE | I/P : 230 VAC O/P : FULL LOAD | O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down | P |
| 4 | SHORT PROTECTION | SHORT EVERY OUTPUT 1 HOUR NO DAMAGE | I/P : 305 VAC O/P : FULL LOAD Ta : 25°C | NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed. | P |

COMPONENT STRESS TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|--|---------------------------------------|--|--|---------|
| 1 | Power Transistor (D to S) or (C to E) Peak Voltage | U2 Rated : IP7518: 700V / 2A | I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C | (1) 632 V (2) 494 V (3) 630 V | P |
| 2 | Diode Peak Voltage | D101 Rated : V30150C: 150V / 30A | I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C | (1) 119 V (2) 89.6 V (3) 114 V | P |
| 3 | Input Capacitor Voltage | C5 Rated : 22u/450V 105°C 16*20 RH | I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C | (1) 434 V (2) 442 V (3) 430 V | P |
| 4 | Control IC Voltage Test | U 2 Rated : IP7518:30V | I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C | (1) 20.5 V (2) 13.9 V (3) 19.0 V | P |
| 5 | Power Transistor (D to S) or (C to E) Peak Voltage | Q1 Rated : NDF10N60ZG: 600V/ 10 A | I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C | (1) 460 V (2) 448 V (3) 458 V | P |

■ SAFETY & E.M.C. TEST

SAFETY TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|----------------------|--|---------------------------------------|-------------------------------------|---------|
| 1 | WITHSTAND VOLTAGE | I/P-O/P : 3.75 KVAC/min | I/P-O/P : 4 KVAC/min Ta : 25°C | I/P-O/P : 1.486 mA NO DAMAGE | P |
| 2 | ISOLATION RESISTANCE | I/P-O/P : 500VDC>100MΩ | I/P-O/P : 500 VDC Ta : 25°C/70% RH | I/P-O/P : >9999 MΩ NO DAMAGE | P |
| 3 | APPROVAL | TUV : Certificate NO : UL : File NO : | | | N/A |

E.M.C TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|---|--|--|-------------------------------|---------|
| 1 | HARMONIC | EN61000-3-2 CLASS C | I/P:230VAC/240VAC/220VAC50HZ O/P:100%,75%,50%LOAD CLASS C ≥ 50% Ta:25°C | PASS | P |
| 2 | CONDUCTION | EN55015 | I/P: 230 VAC (50HZ)/115V[60HZ] O/P:FULL/50% LOAD Ta:25°C | PASS Test by certified Lab | P |
| 3 | RADIATION | EN55015 | I/P: 230 VAC (50HZ)/115V[60HZ] O/P: FULL/50% LOAD Ta:25°C | PASS Test by certified Lab | P |
| 4 | E.S.D | EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV | I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C | CRITERIA A | P |
| 5 | E.F.T | EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV | I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C | CRITERIA A | P |
| 6 | SURGE | IEC61000-4-5 INDUSTRY L-N :2KV | I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C | CRITERIA A | P |
| 7 | Test by certified Lab & Test Report Prepare | | | | |

■ RELIABILITY TEST

ENVIRONMENT TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|---|--|---|-------------------|---------|
| 1 | TEMPERATURE RISE TEST | MODEL : LPF-25D-24 1. ROOM AMBIENT BURN-IN : 2.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=35.0 °C 2. HIGH AMBIENT BURN-IN : 3.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=53.6 °C | | | P |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| 2 | LOW TEMPERATURE TURN ON TEST | TURN ON AFTER 2 HOUR | I/P : 305VAC/100VAC O/P : 95 % LOAD Ta= -40°C | TEST : OK | P |
| 3 | HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST | AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE | I/P : 305 VAC O/P : 95% LOAD Ta= 50 °C HUMIDITY= 95 %R.H | TEST : OK | P |
| 4 | TEMPERATURE COEFFICIENT | ± 0.03 %(0~50°C) | I/P : 230 VAC O/P : 95% LOAD | ± 0.018 %(0~50°C) | P |
| 5 | STORAGE TEMPERATURE TEST | 1. Thermal shock Temperature : -45°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC | | OK | P |
| 6 | THERMAL SHOCK TEST | 1. Thermal shock Temperature : -45°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec | | OK | P |
| 7 | VIBRATION TEST | 1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C | | TEST : OK | P |



| | | | | |
|----|-----------------------------|--|---|---|
| 8 | CAPACITOR LIFE CYCLE | LPF-25D-24:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50 °C LIFE TIME | (1) 606419.2 HRS (2) 80620.8 HRS (3) 146406.4 HRS | P |
| 9 | MTBF | Conducted by Parts Stress Analysis Prediction 3574.2K hrs min. Telcordia SR-332 (Bellcore); 391.6K hrs min. MIL-HDBK-217F (25°C) | | P |
| 10 | DMTBF/Accelerated Life Test | Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Tcase70°C | | P |

| SAMPLE | TEST RESULT | TESTER | APPROVAL |
|----------------|-------------|--------|----------|
| PRODUCT SAMPLE | PASS | ZOULF | HOWAY |

2009/08/04 A50-F023