



Test Report: LPF-25D-36

25W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 250 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 30 mVp-p (Max)	P
2	CONSTANT CURRENT REGION	V1= 18V~36V	I/P : 230VAC O/P : CV MODE Ta : 25°C	O/P= 18V : 0.729 A O/P= 35V : 0.726 A	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 4 %~ -4 % (Max)	I/P : 100 VAC / 305 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.178 %~ -0.061 %	P
4	LINE REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 100 VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.003 %~ -0.003 %	P
5	LOAD REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.031 %~ -0.031 %	P
6	SET UP TIME	230VAC : 500 ms (Max) 115VAC : 1500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 283.816 ms 115VAC/ 219.599 ms	P
7	RISE TIME	230VAC : 80 ms (Max) 115VAC : 80 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 19 ms 115VAC/ 19 ms	P
8	HOLD UP TIME	230VAC : 16 ms (TYP) 115VAC : 16 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 78 ms 115VAC/ 78 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
10	DYNAMIC LOAD	V1 : 3600 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 253 mVp-p (2) 418 mVp-p	P

11	DIMMER TEST	<p>SPEC: *Output constant current level can be adjusted through output cable by 1 ~ 10Vdc, PWM signal or resistor between ADJ1(+) and ADJ2(-). *Reference resistance value for output current adjustment (Typical)</p>																																									
		<table border="1"> <tr> <td>Resistance value</td> <td>10K</td> <td>20K</td> <td>30K</td> <td>40K</td> <td>50K</td> <td>60K</td> <td>70K</td> <td>80K</td> <td>90K</td> <td>100K</td> </tr> <tr> <td>Output current</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>										Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																															
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																															
		<p>*1 ~ 10V dimming function for output current adjustment (Typical)</p>																																									
		<table border="1"> <tr> <td>Dimming value</td> <td>1V</td> <td>2V</td> <td>3V</td> <td>4V</td> <td>5V</td> <td>6V</td> <td>7V</td> <td>8V</td> <td>9V</td> <td>10V</td> </tr> <tr> <td>Output current</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>										Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																															
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																															
		<p>*10V PWM signal for output current adjustment (Typical)</p>																																									
		<table border="1"> <tr> <td>Duty value</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> <tr> <td>Output current</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>										Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																															
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																	
<p>TEST RESULT: I/P : 230 VAC ; Ta : 25°C</p>																																											
<table border="1"> <tr> <td rowspan="3">1</td> <td>Resistance value</td> <td>10K</td> <td>20K</td> <td>30K</td> <td>40K</td> <td>50K</td> <td>60K</td> <td>70K</td> <td>80K</td> <td>90K</td> <td>100K</td> </tr> <tr> <td>Output current</td> <td>0.060A</td> <td>0.127A</td> <td>0.195A</td> <td>0.271A</td> <td>0.344A</td> <td>0.410A</td> <td>0.481A</td> <td>0.549A</td> <td>0.623A</td> <td>0.688A</td> </tr> <tr> <td>%</td> <td>8.57%</td> <td>18.14%</td> <td>27.86%</td> <td>38.71%</td> <td>49.14%</td> <td>58.57%</td> <td>68.71%</td> <td>78.43%</td> <td>89.00%</td> <td>98.29%</td> </tr> </table>										1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	0.060A	0.127A	0.195A	0.271A	0.344A	0.410A	0.481A	0.549A	0.623A	0.688A	%	8.57%	18.14%	27.86%	38.71%	49.14%	58.57%	68.71%	78.43%	89.00%	98.29%
1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K		90K	100K																															
	Output current	0.060A	0.127A	0.195A	0.271A	0.344A	0.410A	0.481A	0.549A		0.623A	0.688A																															
	%	8.57%	18.14%	27.86%	38.71%	49.14%	58.57%	68.71%	78.43%	89.00%	98.29%																																
<table border="1"> <tr> <td rowspan="3">2</td> <td>Dimming value</td> <td>1V</td> <td>2V</td> <td>3V</td> <td>4V</td> <td>5V</td> <td>6V</td> <td>7V</td> <td>8V</td> <td>9V</td> <td>10V</td> </tr> <tr> <td>Output current</td> <td>0.063A</td> <td>0.130A</td> <td>0.200A</td> <td>0.276A</td> <td>0.349A</td> <td>0.413A</td> <td>0.485A</td> <td>0.552A</td> <td>0.625A</td> <td>0.691A</td> </tr> <tr> <td>%</td> <td>9.00%</td> <td>18.57%</td> <td>28.57%</td> <td>39.43%</td> <td>49.86%</td> <td>59.00%</td> <td>69.29%</td> <td>78.86%</td> <td>89.29%</td> <td>98.71%</td> </tr> </table>										2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	0.063A	0.130A	0.200A	0.276A	0.349A	0.413A	0.485A	0.552A	0.625A	0.691A	%	9.00%	18.57%	28.57%	39.43%	49.86%	59.00%	69.29%	78.86%	89.29%	98.71%
2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V		9V	10V																															
	Output current	0.063A	0.130A	0.200A	0.276A	0.349A	0.413A	0.485A	0.552A		0.625A	0.691A																															
	%	9.00%	18.57%	28.57%	39.43%	49.86%	59.00%	69.29%	78.86%	89.29%	98.71%																																
<table border="1"> <tr> <td rowspan="3">3</td> <td>Duty value</td> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> <tr> <td>Output current</td> <td>0.061A</td> <td>0.132A</td> <td>0.203A</td> <td>0.274A</td> <td>0.346A</td> <td>0.417A</td> <td>0.488A</td> <td>0.560A</td> <td>0.631A</td> <td>0.695A</td> </tr> <tr> <td>%</td> <td>8.71%</td> <td>18.86%</td> <td>29.00%</td> <td>39.14%</td> <td>49.43%</td> <td>59.57%</td> <td>69.71%</td> <td>80.00%</td> <td>90.14%</td> <td>99.29%</td> </tr> </table>										3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	0.061A	0.132A	0.203A	0.274A	0.346A	0.417A	0.488A	0.560A	0.631A	0.695A	%	8.71%	18.86%	29.00%	39.14%	49.43%	59.57%	69.71%	80.00%	90.14%	99.29%
3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%		90%	100%																															
	Output current	0.061A	0.132A	0.203A	0.274A	0.346A	0.417A	0.488A	0.560A		0.631A	0.695A																															
	%	8.71%	18.86%	29.00%	39.14%	49.43%	59.57%	69.71%	80.00%	90.14%	99.29%																																

P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V=97 V HIGH-LINE=305 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	85 V~305V TEST : OK	P
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 305 VAC O/P : FULL-MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.97 / 115 VAC(TYP) 0.92 / 277 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.969 / 100% PF= 0.996 / 100% PF= 0.941 / 100%	P
4	EFFICIENCY	85.5% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	85.52 %	P
5	INPUT CURRENT	230V/ 0.25 A (TYP) 115V/ 0.4 A (TYP) 277V/ 0.2 A (TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	I = 0.139 A/ 230 VAC I = 0.254 A/ 115 VAC I = 0.121 A/ 277 VAC	P
6	INRUSH CURRENT	230V/ 50 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 39.0 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.75 mA / 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-CASE : 0.003 mA N-CASE : 0.003 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	101.26%/ 230 VAC 101.88%/ 115 VAC Constant Current Limiting ,recovers automatically after fault condition is removed.	P
2	OVER VOLTAGE PROTECTION	CH1 : 41 V ~ 49 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	44.40 V/ 230 VAC 44.40 V/ 115 VAC Shut down and latch off o/p voltage, re-power on to recover	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 95± 5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed.	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U2 Rated : IP7518: 700V / 2A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 652 V (2) 492 V (3) 632 V	P
2	Diode Peak Voltage	D101 Rated : V20200C: 200V / 20A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 162 V (2) 145 V (3) 157 V	P
3	Input Capacitor Voltage	C5 Rated : 22u/450V 105°C 16*20 RH	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 444 V (2) 442 V (3) 432 V	P
4	Control IC Voltage Test	U 2 Rated : IP7518:30V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 19.6 V (2) 13.6 V (3) 19.1 V	P
5	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : NDF10N60ZG: 600V/ 10 A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 526 V (2) 424 V (3) 438 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min	I/P-O/P : 4 KVAC/min Ta : 25°C	I/P-O/P : 1.521 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ	I/P-O/P : 500 VDC Ta : 25°C/70% RH	I/P-O/P : >9999 MΩ NO DAMAGE	P
3	APPROVAL	TUV : Certificate NO : UL : File NO :			N/A

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:230VAC/240VAC/220VAC50HZ O/P:100%,75%,50%LOAD CLASS C ≥ 50% Ta:25°C	PASS	P
2	CONDUCTION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P: FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	MODEL : LPF-25D-24 1. ROOM AMBIENT BURN-IN : 2.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=35.0 °C 2. HIGH AMBIENT BURN-IN : 3.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=53.6 °C			P
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 95 % LOAD Ta= -40°C	TEST : OK	P
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 305 VAC O/P : 95% LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P
4	TEMPERATURE COEFFICIENT	± 0.03 %(0~50°C)	I/P : 230 VAC O/P : 95% LOAD	± 0.018 %(0~50°C)	P
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C		TEST : OK	P



8	CAPACITOR LIFE CYCLE	LPF-25D-24:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50 °C LIFE TIME	(1) 606419.2 HRS (2) 80620.8 HRS (3) 146406.4 HRS	P
9	MTBF	Conducted by Parts Stress Analysis Prediction 3574.2K hrs min. Telcordia SR-332 (Bellcore); 391.6K hrs min. MIL-HDBK-217F (25°C)		P
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Tcase70°C		P

SAMPLE	TEST RESULT	TESTER	APPROVAL
PRODUCT SAMPLE	PASS	ZOULF	HOWAY

2009/08/04 A50-F023