



# Test Report : SPA01B-15

---

1W DC-DC Regulated Single Output Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety Test

## ■ RELIABILITY TEST

Environment Test

Otehr

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2 % ~ +2 % (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	-0.48 %	P
2	RIPPLE & NOISE	80 mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	25 mV	P
3	LINE REGULATION	-0.5 % ~ +0.5 % (Max)	I/P:18VDC~36VDC O/P:FULL LOAD Ta:25°C	-0.03 % ~ +0.00%	P
4	LOAD REGULATION	-0.5 % ~ +0.5 % (Max)	I/P:24VDC O/P:MIN~FULL LOAD Ta:25°C	-0.02 % ~ +0.02 %	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	14.0 ~ 36VDC	P
2	EFFICIENCY	79 % (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	79.60 %	P
3	DC CURRENT	55 mA / FULL LOAD (Max) 10 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	53.0 mA / FULL LOAD 9 mA / NO LOAD	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	130%~200 % (Typ)	I/P:24VDC O/P:TESTING Ta:25°C	182% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

**SAFETY TEST**
**SAFETY TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

**RELIABILITY TEST**
**ENVIRONMENT TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 15HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 45HRS I/P:24VDC O/P:FULL LOAD Ta=85°C			P								
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>35.9°C</td> <td>97.5°C</td> </tr> </tbody> </table>		NO	Position	1	2	1	CASE	35.9°C	97.5°C		
NO	Position	1	2										
1	CASE	35.9°C	97.5°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 13 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

**OTHER**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 1.91624 M.T.B.F : 521855 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	PETER CHENG	VINCENT TSENG